
INKER & RASOR

KE

O BATTERY RELEASE BELOW



MODEL APS Holiday Detector 800v to 35,000v

SAFETY SHUT OFF, INTEGRATED VOLTMETER, LED HOLIDAY INDICATOR, ERGONOMIC DESIGN, VOLUME CONTROL AND A <u>NEW, LIGHTWEIGHT,</u> LONG LIFE BATTERY

Info@tinker-rasor.com

DESIGNED WITH SAFETY IN MIND!





Distributed by

TECNOLOGÍA TOTAL INGENIERÍA EN INTEGRIDAD Y CORROSIÓN www.tecnologiatotal.net



Integrated voltmeter povides measured output voltage. No need for additional, separate voltmeter for verification

Instrument will work only when

safety handle is depressed.

www.teststations.com

www.tinker-rasor.com

Info@tinker-rasor.com

www.detectron.com



Tinker & Rasor quality is found in our products, our people and our customer service.



PRODUCT DATA SHEET MODEL APS HOLIDAY DETECTOR

Features:

- SAFETY SWITCH INSTANT SHUT OFF
- Updated Battery light weight, longer life
- 800v 35000v in one instrument
- Integrated Voltmeter
- Volume adjustment for use in loud environments
- Super Bright visual holiday indicator
- Ergonomic handle and grip
- Low battery voltage indicator
- Regulated voltage
- Push button operation

Construction:

- Rugged design for long life
- Water & Dust Resistant Carrying Case
- Weather sealed
- Solid state electronics

Applications:

- Pipelines and other coated structures
- Wide variety of coatings materials
- Thin to thick coatings
- Conforms to NACE International SP0188, SP0274, Sp0490 Also to many ASTM, SSPC, ISO, etc

Specifications:

- Pulse DC output voltage
- Low: 800v to 8,000v
- High: 3,500v to 35,000v
- 100v Resolution (Voltmeter)
- +/- 5% Accuracy
- Battery operated (6v)
- 110/220v AC Charger

Dimensions:

- 2.5" x 21.5" x 2.75" Instrument only
- 5" x 2.5" x 5.5" Battery box

Carrying Case:

40.5" x 17" x 7" (1028.7 x 431.8 x 177.8 mm) 40 lbs. (18.14kg) Shipping Weight* *Weight will vary based upon electrode choices

DELIVERY: Immediately from STOCK ExWorks San Bernardino, CA USA SERVICE: 24-hour Turn-Around TERMS: Net30 Days, on approval of credit WARRANTY: 3 Years, parts and labor



Kit Includes: Instrument (2) Batteries, w/ Cover Ground Cable Wand Handle Inspection Paddle Carrying Case Instruction Manual Letter of Calibration

Electrode (Choose One): Full Circle Spring Electrode for any one pipe diameter between 2" and 36"

Half Circle Spring Electrode for any one pipe, 0.75" and 8"

Silicone-Rubber Brush Electrode with any one width between 2" and 8"

MODEL APS HOLIDAY DETECTOR

AVAILABLE FROM STOCK